

In the claims:

Please substitute the following full listing of claims for the claims as originally filed or most recently amended.

A 1. (Currently amended) A folding type portable communication device, comprising:

two communication units connected to each other in a foldable manner and having a folded position and an unfolded position;

a two-level switch for detecting which one of the folded and unfolded position the two communication units have, the switch providing a first level when the two communication units have the folded position and a second level when the two communication units have the unfolded position;

a vibrator;

a sounder;

a mode selector operatively coupled with the two-level switch, the vibrator and the sounder for selectively providing setting for one of a calling reception vibration mode and a sound mode in response to the level provided by the two-level switch,

the mode selector including a first circuit for driving the vibrator when energized and a second circuit for driving the sounder when energized;

the mode selector including a controller for energizing the first circuit upon reception of a calling when the setting for the calling reception vibration mode is provided and the second circuit upon reception of a calling when the setting for the calling reception sound mode is provided.

2. (Currently amended) A folding type portable communication device as claimed in claim 1, wherein the controller energizes the first circuit upon reception of a calling when the two-level switch provides the

first level indicating that the two communication units have the folded position, and where the controller energizes the second ~~controller~~ circuit upon reception of a calling when the two-level switch provides the second level indicating that the two communication units have the unfolded position.

A 3. (Currently amended) A folding type portable communication device as claimed in claim 1, wherein the controller energizes the first circuit upon reception of a calling when the two-level switch provides the second level indicating that the two communication units have the unfolded position, and where the controller energizes the second ~~controller~~ circuit upon reception of a calling when the two-level switch provides the first level indicating that the two communication units have the folded position.

4. (Currently amended) A folding type portable communication device as claimed in claim 1, wherein the mode selector includes a memory coupled with the controller, and wherein the memory stores the settings for the calling reception vibration mode and calling reception sound mode.

5. (Original) A folding type portable communication device as claimed in claim 1, wherein the two-level switch includes a magnet mounted within one of the two communication units and a detector mounted within the other communication unit for detecting a magnetic field provided by the magnet.

6. (Original) A folding type portable communication device as claimed in claim 5, wherein the magnet is brought into registry with the detector when the two communication units have the folded position.

A 7. (Currently amended) A method of controlling a selection between a calling reception vibration mode and a calling reception sound mode of a folding type portable communication device that has two communication units connected to each other in a foldable manner and having a folded position and an unfolded position, the method comprising;

detecting which one of the folded and unfolded position the two communication units have;

providing setting for the calling reception vibration mode upon detecting the folded position; and

providing setting for the calling reception sound mode upon detecting the unfolded position.

---